



iM2600

Medium Case

Carry-On Case

- Two Press & Pull Latches
- Double-layered, Soft-grip Handle
- Two Padlockable Hasps
- Vortex® Valve
- Flush Powerful Hinges
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

CONFIGURATIONS

iM2600 - Standard

iM2600-X0000 - With No Foam

iM2600-X0002 - With With Padded Dividers

DIMENSIONS

Interior (L x W x D): 20.00 x 14.00" x 7.70 (50.8 x 35.6 x 19.6 cm)

Exterior (L x W x D): 21.20 x 16.00" x 8.30 (53.8 x 40.6 x 21.1 cm)

Lid Depth: 2.00" (5.1 cm)

Bottom Depth: 5.70" (14.5 cm)

Total Depth: 7.7" (19.6 cm)

Int Volume: 1.25 ft³ (0.035 m³)

MATERIALS

Body: Injection Molded HPX® high performance resin

Latch: Valox - Polybutylene Terephthalate (PBT)

Latch (Alt): Xenoy - Polyester/Polycarbonate blend

O-Ring: EPDM

Pins: Stainless Steel

Pins (Alt): Aluminum

Foam: 1.3/1.35 polyester

Purge Body: Valox - Polybutylene Terephthalate (PBT)

Purge Body (Alt): Xenoy - Polyester/Polycarbonate blend

Purge Vent: Gortex membrane

COLORS

■ Black

■ Yellow

■ OD Green

WEIGHT

Weight With Foam: 11.60 lbs (5.3 kg)

Weight Without Foam: 8.50 lbs (3.9 kg)

Buoyancy: 79.81 lbs (36.2 kg)

Master Pack Weight: 24.20 lbs (11 kg)

TEMPERATURE

Minimum Temperature: -20°

Maximum Temperature: 140°

CERTIFICATIONS

MIL-STD-810F

ATA 300

FED-STD-101C

FOAM PROPERTIES

Layer 1 (Lid): 2.00" Convolute

Layer 2 (Base): 0.63" Pad

Layer 3 (Base): 1.75" Pick N Pluck

Layer 4 (Base): 1.75" Pick N Pluck

Layer 5 (Base): 1.75" Pick N Pluck

OTHER

Master Pack: 2

Military: yes

Pelican Products, Inc.

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com