iM2875

Large Case

Travel Case

- Six Press & Pull Latches
- Three Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- In-line Wheels
- Telescoping Handle
- Vortex® Valve
- Flush Powerful Hinges
- Lightweight Strong HPX® Resin
- Watertight
- Dustproof
- Guaranteed For Life

CONFIGURATIONS

iM2875 - Standard
iM2875-X0000 - With No Foam
iM2875-X0002 - With With Padded Dividers

DIMENSIONS

Interior (L x W x D): 22.50 x 21.10" x 11.40 (57.2 x 53.6 x 29 cm)
Exterior (L x W x D): 24.90 x 23.70" x 13.10 (63.2 x 60.2 x 33.3 cm)
Lid Depth: 2.00" (5.1 cm)
Bottom Depth: 9.40" (23.9 cm)
Total Depth: 11.4" (29 cm)
Int Volume: 3.13 ft³ (0.089 m³)

MATERIALS

Body: Injection Molded HPX® high performance resin
Latch: Valox - Polybutylene Terephthalate (PBT)
Latch (Alt): Xenoy - Polyester/Polycarbonate blend
O-Ring: EPDM
Pins: Stainless Steel
Pins (Alt): Aluminum
Foam: 1.3/1.35 polyester
Purge Body: Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt): Xenoy - Polyester/Polycarbonate blend
Purge Vent: Gortex membrane

COLORS

Black

OD Green

WEIGHT

Weight With Foam: 24.60 lbs (11.2 kg)
Weight Without Foam: 20.10 lbs (9.1 kg)
Buoyancy: 194.16 lbs (88.1 kg)
Master Pack Weight: 32.00 lbs (14.5 kg)

TEMPERATURE

Minimum Temperature: -20°
Maximum Temperature: 140°

CERTIFICATIONS

MIL-STD-810F
ATA 300
FED-STD-101C

FOAM PROPERTIES

Layer 1 (Lid): 2.00" Convolute
Layer 2 (Base): 0.63" Pad
Layer 3 (Base): 1.78" Pick N Pluck
Layer 4 (Base): 1.78" Pick N Pluck
Layer 5 (Base): 1.78" Pick N Pluck
Layer 6 (Base): 1.78" Pick N Pluck
Layer 7 (Base): 1.78" Pick N Pluck

OTHER

Extendable Handle: yes
Master Pack: 1
Military: yes

Pelican Products, Inc.
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com