



iM2975

Large Case

Travel Case



- Five Press & Pull Latches
- Three Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- In-line Wheels
- Telescoping Handle
- Vortex® Valve
- Flush Powerful Hinges
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

CONFIGURATIONS

iM2975 - Standard

iM2975-X0000 - With No Foam

iM2975-X0002 - With With Padded Dividers

DIMENSIONS

Interior (L x W x D): 29.00 x 18.00" x 13.80 (73.7 x 45.7 x 35.1 cm)

Exterior (L x W x D): 31.30 x 20.40" x 15.50 (79.5 x 51.8 x 39.4 cm)

Lid Depth: 2.00" (5.1 cm)

Bottom Depth: 11.80" (30 cm)

Total Depth: 13.8" (35.1 cm)

Int Volume: 4.17 ft³ (0.118 m³)

MATERIALS

Body: Injection Molded HPX® high performance resin

Latch: Valox - Polybutylene Terephthalate (PBT)

Latch (Alt): Xenoy - Polyester/Polycarbonate blend

O-Ring: EPDM

Pins: Stainless Steel

Pins (Alt): Aluminum

Foam: 1.3/1.35 polyester

Purge Body: Valox - Polybutylene Terephthalate (PBT)

Purge Body (Alt): Xenoy - Polyester/Polycarbonate blend

Purge Vent: Gortex membrane

COLORS



Black



OD Green

WEIGHT

Weight With Foam: 29.50 lbs (13.4 kg)

Weight Without Foam: 22.80 lbs (10.3 kg)

Buoyancy: 250.02 lbs (113.4 kg)

Master Pack Weight: 31.50 lbs (14.3 kg)

TEMPERATURE

Minimum Temperature: -20°

Maximum Temperature: 140°

CERTIFICATIONS

MIL-STD-810F

ATA 300

FED-STD-101C

FOAM PROPERTIES

Layer 1 (Lid): 2.00" Convolute

Layer 2 (Base): 0.63" Pad

Layer 3 (Base): 1.88" Pick N Pluck

Layer 4 (Base): 1.88" Pick N Pluck

Layer 5 (Base): 1.88" Pick N Pluck

Layer 6 (Base): 1.88" Pick N Pluck

Layer 7 (Base): 1.88" Pick N Pluck

Layer 8 (Base): 1.88" Pick N Pluck

OTHER

Extendable Handle: yes

Master Pack: 1

Military: yes

Pelican Products, Inc.

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com