



## iM2200

### Medium Case



- Two Press & Pull Latches
- Double-layered, Soft-grip Handle
- Two Padlockable Hasps
- Vortex® Valve
- Flush Powerful Hinges
- **Meets airline regulations for carry-on luggage\***
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life
- \*Check with your airline for exact measurement requirements

## CONFIGURATIONS

**iM2200** - Standard

**iM2200-X0000** - With No Foam

**iM2200-X0002** - With With Padded Dividers

## DIMENSIONS

**Interior (L x W x D):** 15.00 x 10.50" x 6.00 (38.1 x 26.7 x 15.2 cm)

**Exterior (L x W x D):** 16.20 x 12.70" x 6.60 (41.1 x 32.3 x 16.8 cm)

**Lid Depth:** 2.00" (5.1 cm)

**Bottom Depth:** 4.00" (10.2 cm)

**Total Depth:** 6" (15.2 cm)

**Int Volume:** 0.55 ft<sup>3</sup> (0.016 m<sup>3</sup>)

## MATERIALS

**Body:** Injection Molded HPX® high performance resin

**Latch:** Valox - Polybutylene Terephthalate (PBT)

**Latch (Alt):** Xenoy - Polyester/Polycarbonate blend

**O-Ring:** EPDM

**Pins:** Stainless Steel

**Pins (Alt):** Aluminum

**Foam:** 1.3/1.35 polyester

**Purge Body:** Valox - Polybutylene Terephthalate (PBT)

**Purge Body (Alt):** Xenoy - Polyester/Polycarbonate blend

**Purge Vent:** Gortex membrane

## COLORS

■ Black

■ Yellow

## WEIGHT

**Weight With Foam:** 6.10 lbs (2.8 kg)

**Weight Without Foam:** 4.90 lbs (2.2 kg)

**Buoyancy:** 35.50 lbs (16.1 kg)

**Master Pack Weight:** 28.60 lbs (13 kg)

## TEMPERATURE

**Minimum Temperature:** -20°

**Maximum Temperature:** 140°

## CERTIFICATIONS

MIL-STD-810F

ATA 300

FED-STD-101C

## FOAM PROPERTIES

**Layer 1 (Lid):** 2.00" Convolute

**Layer 2 (Base):** 0.63" Pad

**Layer 3 (Base):** 1.75" Pick N Pluck

**Layer 4 (Base):** 1.75" Pick N Pluck

## OTHER

**Master Pack:** 4

**Military:** yes

**Pelican Products, Inc.**

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)