



iM3100

Large Case

Long Gun Case



- Six Press & Pull Latches
- Two Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- In-line Wheels
- Vortex® Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

CONFIGURATIONS

iM3100 - Standard

iM3100-X0000 - With No Foam

DIMENSIONS

Interior (L x W x D): 36.50 x 14.00" x 6.00 (92.7 x 35.6 x 15.2 cm)

Exterior (L x W x D): 39.80 x 16.50" x 6.70 (101.1 x 41.9 x 17 cm)

Lid Depth: 2.00" (5.1 cm)

Bottom Depth: 4.00" (10.2 cm)

Total Depth: 6" (15.2 cm)

Int Volume: 1.77 ft³ (0.05 m³)

MATERIALS

Body: Injection Molded HPX® high performance resin

Latch: Valox - Polybutylene Terephthalate (PBT)

Latch (Alt): Xenoy - Polyester/Polycarbonate blend

O-Ring: EPDM

Pins: Stainless Steel

Pins (Alt): Aluminum

Foam: 1.3/1.35 polyester

Purge Body: Valox - Polybutylene Terephthalate (PBT)

Purge Body (Alt): Xenoy - Polyester/Polycarbonate blend

Purge Vent: Gortex membrane

COLORS

■ Black

■ OD Green

WEIGHT

Weight With Foam: 19.80 lbs (9 kg)

Weight Without Foam: 15.20 lbs (6.9 kg)

Buoyancy: 113.07 lbs (51.3 kg)

Master Pack Weight: 8.00 lbs (3.6 kg)

TEMPERATURE

Minimum Temperature: -20°

Maximum Temperature: 140°

CERTIFICATIONS

MIL-STD-810F

ATA 300

FED-STD-101C

FOAM PROPERTIES

Layer 1 (Lid): 2.00" Convolute

Layer 2 (Base): 0.50" Pad

Layer 3 (Base): 1.75" Pad

Layer 4 (Base): 1.75" Pad

OTHER

Master Pack: 1

Military: yes

Pelican Products, Inc.

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com