



1400 Small Case

- **Watertight, crushproof, and dustproof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Stainless steel padlock protectors
- Comfortable rubber over-molded handle
- Stainless steel hardware
- Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)

CONFIGURATIONS

1400 - Standard

1400NF - With No Foam

DIMENSIONS

Interior (L x W x D): 11.81 x 8.87" x 5.18 (30 x 22.5 x 13.2 cm)

Exterior (L x W x D): 13.37 x 11.62" x 6.00 (34 x 29.5 x 15.2 cm)

Lid Depth: 1.18"

Bottom Depth: 4.00"

Total Depth: 5.18"

Int Volume: 0.31 ft³

MATERIALS

Body: Polypropylene

Latch: ABS

O-Ring: Polymer

Pins: Stainless Steel


Foam: 1.3 lb Polyurethane

Purge Body: ABS


Purge Vent: 3 Micron Hydrophobic Non-Woven

Purge O-Ring: 70 Shore Nitrile

COLORS




Black




Silver



Orange



Yellow



OD Green



Desert Tan

WEIGHT

Weight With Foam: 4.41 lbs

Weight Without Foam: 3.97 lbs

Buoyancy: 20.06 lbs

Master Pack Weight: 22.60 lbs

TEMPERATURE

Minimum Temperature: -40°

Maximum Temperature: 210°

CERTIFICATIONS

IP67

MIL C-4150J

Def Stan 81-41

STANAG 4280

ATA 300

FOAM PROPERTIES

Layer 1 (Lid): 1.38" Convolute

Layer 2 (Base): 0.50" Pad

Layer 3 (Base): 3.38" Pick N Pluck

OTHER

Master Pack: 4

Nameplate: yes

Military: yes

Pelican Products, Inc.

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com