



1460 Medium Case



- **Top lid opens up to 180° for on-the-field anti-roll stability when open**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handles
- Stainless steel hardware and padlock protectors
- [Personalized nameplate service available](#)
- [Lifetime Guarantee of Excellence](#)
- [Also available with EMS Organizer and Dividers](#)
- **Watertight, crushproof, and dustproof**

CONFIGURATIONS

- 1460** - Standard
- 1460AALG** - With With Custom Foam for 9430 / 9435
- 1460NF** - With No Foam

DIMENSIONS

- Interior (L x W x D):** 18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm)
- Exterior (L x W x D):** 20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)
- Lid Depth:** 4.91"
- Bottom Depth:** 6.01"
- Total Depth:** 10.92"
- Int Volume:** 1.16 ft³


MATERIALS

- Body:** Polypropylene
- Latch:** EXL
- O-Ring:** Polymer
- Pins:** Stainless Steel
- Foam:** Polyurethane
- Purge Body:** ABS
- Purge Vent:** 3 Micron Hydrophobic Non-Woven
- Purge O-Ring:** 70 Shore Nitrile

COLORS



Black



OD Green



Desert Tan

WEIGHT

Weight With Foam: 12.48 lbs

Weight Without Foam: 8.75 lbs

Buoyancy: 82.00 lbs

TEMPERATURE

Minimum Temperature: -40°

Maximum Temperature: 210°

CERTIFICATIONS

IP67

FOAM PROPERTIES

Layer 1 (Lid): 1.60" Pick N Pluck

Layer 2 (Base): 1.38" Pick N Pluck

Layer 3 (Base): 2.20" Pick N Pluck

Layer 4 (Base): 2.20" Pick N Pluck

Layer 5 (Base): 2.20" Pick N Pluck

Layer 6 (Base): 2.20" Pick N Pluck

OTHER

Military: yes

Pelican Products, Inc.

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com