



1690

Large Case

Transport Case



- Retractable extension handle
- 4 strong polyurethane wheels with stainless steel bearings
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Large 2-person fold down handles
- Stainless steel padlock protectors
- 3 level Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- **Watertight, crushproof, and dustproof**

CONFIGURATIONS

- 1690** - Standard
- 1694** - With With Padded Dividers
- 1690NF** - With No Foam

DIMENSIONS

- Interior (L x W x D):** 30.13 x 25.13" x 15.36 (76.5 x 63.8 x 39 cm)
- Exterior (L x W x D):** 33.43 x 28.40" x 17.65 (84.9 x 72.1 x 44.8 cm)
- Lid Depth:** 2.86"
- Bottom Depth:** 12.14"
- Total Depth:** 15"
- Int Volume:** 6.73 ft³


MATERIALS

- Body:** Polypropylene
- Latch:** ABS
- O-Ring:** Polymer
- Pins:** Stainless Steel
- Foam:** 1.3 lb Polyurethane
- Purge Body:** ABS
- Purge Vent:** 3 Micron Hydrophobic Non-Woven
- Purge O-Ring:** 70 Shore Nitrile

COLORS



Black



OD Green



Desert Tan

WEIGHT

Weight With Foam: 43.00 lbs

Weight Without Foam: 34.00 lbs

Buoyancy: 433.00 lbs

Master Pack Weight: 52.27 lbs

TEMPERATURE

Minimum Temperature: -40°

Maximum Temperature: 210°

CERTIFICATIONS

IP67

Def Stan 81-41

STANAG 4280

FOAM PROPERTIES

Layer 1 (Lid): 3.00" Convolute

Layer 2 (Base): 1.25" Pad

Layer 3 (Base): 3.65" Pick N Pluck

Layer 4 (Base): 3.65" Pick N Pluck

Layer 5 (Base): 3.65" Pick N Pluck

OTHER

Extendable Handle: yes

Master Pack: 1

Nameplate: yes

Reduced Area: yes

Pelican Products, Inc.

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com