



1630

Large Case

Transport Case



- Retractable extension handle
- 4 strong polyurethane wheels with stainless steel bearings (wheel diameter is 5.3cm)
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Fold down handles
- Stainless steel padlock protectors
- 3 level Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- Stackable
- Reinforced corners
- [Lifetime Guarantee of Excellence](#)
- **Watertight, crushproof, and dustproof**
- Note: Please consult a sales specialist for more details.

CONFIGURATIONS

- 1630** - Standard
- 1634** - With With Padded Dividers
- 1630NF** - With No Foam

DIMENSIONS

- Interior (L x W x D):** 27.70 x 20.98" x 15.50 (70.4 x 53.3 x 39.4 cm)
- Exterior (L x W x D):** 31.28 x 24.21" x 17.48 (79.5 x 61.5 x 44.4 cm)
- Lid Depth:** 3.25"
- Bottom Depth:** 12.14"
- Total Depth:** 15.39"
- Int Volume:** 5.21 ft³


MATERIALS

- Body:** Polypropylene
- Latch:** ABS
- O-Ring:** Polymer
- Pins:** Stainless Steel
- Foam:** 1.3 lb Polyurethane
- Purge Body:** ABS
- Purge Vent:** 3 Micron Hydrophobic Non-Woven
- Purge O-Ring:** 70 Shore Nitrile

COLORS



Black



OD Green



Desert Tan

WEIGHT

Weight With Foam: 36.00 lbs

Weight Without Foam: 31.00 lbs

Buoyancy: 350.00 lbs

Master Pack Weight: 42.00 lbs

TEMPERATURE

Minimum Temperature: -40°

Maximum Temperature: 210°

CERTIFICATIONS

IP67

Def Stan 81-41

STANAG 4280

FOAM PROPERTIES

Layer 1 (Lid): 3.20" Pad

Layer 2 (Base): 1.00" Pad

Layer 3 (Base): 3.75" Pick N Pluck

Layer 4 (Base): 3.75" Pick N Pluck

Layer 5 (Base): 3.75" Pick N Pluck

OTHER

Wheels: 4

Extendable Handle: yes

Master Pack: 1

Nameplate: yes

Reduced Area: yes

Pelican Products, Inc.

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com