



1610 Large Case

- Retractable extension handle
- Strong polyurethane wheels with stainless steel bearings
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Fold down handles
- Stainless steel hardware and padlock protectors
- 3 level Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- **Watertight, crushproof, and dustproof**

CONFIGURATIONS

- 1610** - Standard
- 1614** - With With Padded Dividers
- 1610NF** - With No Foam
- 1610TP** - With With TrekPak Divider System

DIMENSIONS

- Interior (L x W x D):** 21.78 x 16.69" x 10.62 (55.3 x 42.4 x 27 cm)
- Exterior (L x W x D):** 24.83 x 19.69" x 11.88 (63.1 x 50 x 30.2 cm)
- Lid Depth:** 2.05"
- Bottom Depth:** 8.57"
- Total Depth:** 10.62"
- Int Volume:** 2.23 ft³

MATERIALS

- Body:** Polypropylene
- Latch:** ABS
- O-Ring:** Polymer
- Pins:** Stainless Steel
- Foam:** 1.3 lb Polyurethane
- Purge Body:** ABS
- Purge Vent:** 3 Micron Hydrophobic Non-Woven
- Purge O-Ring:** 70 Shore Nitrile

COLORS



Black



OD Green



Desert Tan

WEIGHT

Weight With Foam: 22.30 lbs

Weight Without Foam: 19.50 lbs

Buoyancy: 119.93 lbs

Master Pack Weight: 25.55 lbs

TEMPERATURE

Minimum Temperature: -40°

Maximum Temperature: 210°

CERTIFICATIONS

IP67

Def Stan 81-41

STANAG 4280

FOAM PROPERTIES

Layer 1 (Lid): 2.00" Convolute

Layer 2 (Base): 1.50" Pad

Layer 3 (Base): 2.38" Pick N Pluck

Layer 4 (Base): 2.38" Pick N Pluck

Layer 5 (Base): 2.38" Pick N Pluck

OTHER

Wheels: 2

Extendable Handle: yes

Master Pack: 1

Nameplate: yes

Military: yes

Pelican Products, Inc.

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com