



1600 Large Case

- **Watertight, crushproof, and dustproof**
- Open cell core with solid wall design - strong, light weight
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- O-ring seal
- Comfortable rubber over-molded handle
- Stainless steel hardware and padlock protectors
- 2 level Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- [Lifetime Guarantee of Excellence](#)

CONFIGURATIONS

- 1600** - Standard
- 1604** - With With Padded Dividers
- 1600NF** - With No Foam
- 1600TP** - With With TrekPak Divider System

DIMENSIONS

- Interior (L x W x D):** 21.51 x 16.54" x 7.99 (54.6 x 42 x 20.3 cm)
- Exterior (L x W x D):** 24.39 x 19.36" x 8.79 (62 x 49.2 x 22.3 cm)
- Lid Depth:** 1.75"
- Bottom Depth:** 6.12"
- Total Depth:** 7.87"
- Int Volume:** 1.65 ft³


MATERIALS

- Body:** Polypropylene
- Latch:** ABS
- O-Ring:** Polymer
- Pins:** Stainless Steel
- Foam:** 1.3 lb Polyurethane
- Purge Body:** ABS
- Purge Vent:** 3 Micron Hydrophobic Non-Woven
- Purge O-Ring:** 70 Shore Nitrile


COLORS




Black




Silver



Orange



Yellow



OD Green



Desert Tan

WEIGHT

Weight With Foam: 14.11 lbs

Weight Without Foam: 13.00 lbs

Buoyancy: 117.00 lbs

Master Pack Weight: 34.75 lbs

TEMPERATURE

Minimum Temperature: -40°

Maximum Temperature: 210°

CERTIFICATIONS

IP67

MIL C-4150J

Def Stan 81-41

STANAG 4280

ATA 300

FOAM PROPERTIES

Layer 1 (Lid): 2.00" Convolute

Layer 2 (Base): 1.00" Pad

Layer 3 (Base): 2.38" Pick N Pluck

Layer 4 (Base): 2.38" Pick N Pluck

OTHER

Master Pack: 2

Nameplate: yes

Military: yes

Pelican Products, Inc.

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com