

# AL1212-1904

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.

• Molded-in, tongue-in-groove gasketed parting lines for splash resistance and tight seals, even after impact

• Reinforced corners and edges for additional impact protection

Molded-in ribs and corrugations for secure, non-slip stacking, columnar

strength, and added protection

Recessed hardware for extra protection

• Positive anti-shear locks, which prevent lid separation after impact, and reduce stress on hardware

• Patented molded-in metal inserts for catch and hinge attachment points,

which provide strength and spread loads to the container

• One-piece construction, molded from lightweight, high-impact polyethylene



### DIMENSIONS

Interior (L×W×D)	12.00 x 12.00" x 22.70 (30.5 x 30.5 x 57.7 cm)
Exterior (L×W×D)	15.00 x 15.00" x 24.39 (38.1 x 38.1 x 62 cm)
Lid Depth	4.00" (10.2 cm)
Bottom Depth	18.70" (47.5 cm)
Total Depth	22.7" (57.7 cm)
Int Volume	1.89 ft <sup>3</sup> (0.054 m <sup>3</sup> )

## MATERIALS

Body	RotoMolded Polyethylene
Latch	Steel (Nickel-black Plated)
O-Ring	Silicone Sponge
Pins	Stainless Steel
Pins (Alt)	Aluminum
Purge Body	Aluminum

## COLOURS

Gray - 133 Fed Std 26270

### WEIGHT

Weight	16.80 lbs (7.6 kg)
Buoyancy	181.47 lbs (82.3 kg)
Master Pack Weight	18.80 lbs (8.5 kg)

## TEMPERATURE

Minimum Temperature-20°F (-28.9 °C)Maximum Temperature140°F (60 °C)

OTHER	
-------	--

Military

yes

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com

Document created on 07-16-20