

# AL3232-1412AC

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.

- Molded-in, tongue-in-groove gasketed parting lines for splash resistance and tight seals, even after impact
- Reinforced corners and edges for additional impact protection
- Molded-in ribs and corrugations for secure, non-slip stacking, columnar strength, and added protection
- Recessed hardware for extra protection
- Positive anti-shear locks, which prevent lid separation after impact, and reduce stress on hardware
- Patented molded-in metal inserts for catch and hinge attachment points, which provide strength and spread loads to the container
- One-piece construction, molded from lightweight, high-impact polyethylene



#### **DIMENSIONS**

Interior (L×W×D) 32.43 x 32.43" x 26.75 (82.4 x 82.4 x 67.9 cm) Exterior (L×W×D) 35.43 x 35.43" x 30.44 (90 x 90 x 77.3 cm)

 Lid Depth
 12.25" (31.1 cm)

 Bottom Depth
 14.50" (36.8 cm)

 Total Depth
 26.75" (67.9 cm)

 Int Volume
 16.28 ft³ (0.461 m³)

## **MATERIALS**

Body RotoMolded Polyethylene
Latch Steel (Nickel-black Plated)

O-Ring Silicone Sponge
Pins Stainless Steel
Pins (Alt) Aluminum
Purge Body Aluminum

# **COLOURS**

Gray - 133 Fed Std 26270

#### WEIGHT

 Weight
 68.40 lbs (31 kg)

 Buoyancy
 1312.16 lbs (595.2 kg)

 Master Pack Weight
 70.40 lbs (31.9 kg)

### **TEMPERATURE**

Minimum Temperature -20°F (-28.9 °C)
Maximum Temperature 140°F (60 °C)

Military

yes

# Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 07-16-20