

AL4024-1305

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.

• Molded-in, tongue-in-groove gasketed parting lines for splash resistance and tight seals, even after impact

• Reinforced corners and edges for additional impact protection

• Molded-in ribs and corrugations for secure, non-slip stacking, columnar strength, and added protection

Recessed hardware for extra protection

• Positive anti-shear locks, which prevent lid separation after impact, and reduce stress on hardware

• Patented molded-in metal inserts for catch and hinge attachment points, which provide strength and spread loads to the container

 One-piece construction, molded from lightweight, high-impact polyethylene



CONFIGURATIONS



AL4024-1305 Standard



AL4024-1305-RP Empty

DIMENSIONS

39.87 x 24.31" x 18.00 (101.3 x 61.7 x 45.7 cm)
42.87 x 27.31" x 20.19 (108.9 x 69.4 x 51.3 cm)
5.25" (13.3 cm)
12.75" (32.4 cm)
18" (45.7 cm)
10.1 ft ³ (0.286 m ³)

MATERIALS

Body	RotoMolded Polyethylene		
Latch	Steel (Nickel-black Plated)		
O-Ring	Silicone Sponge		
Pins	Stainless Steel		
Pins (Alt)	Aluminum		
Purge Body	Aluminum		

COLOURS

Gray - 133 Fed Std 26270

WEIGHT

Weight	50.20 lbs (22.8 kg)	
Buoyancy	803.84 lbs (364.6 kg)	
Master Pack Weight	52.20 lbs (23.7 kg)	

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

OTHER

Military	yes		

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com

 • www.pelican.com

Document created on 07-16-20